

---



# Resealing Joints in PCC Pavements

**Rick Stone**

**General Manager, Cimline Northeast**





# Joint Resealing Overview

- Why seal joints?
- Methods & Materials
- Equipment
- Joint Preparation
- Proper Resealing
- Common Problems
- References / Resources



# JOINT SEALING

- Why Seal?
- To minimize passage of water through joints which leads to pavement deterioration.
- To prevent incompressibles from filling the joints and affecting joint movement and performance.



# Water Passage

- Pumping
- Faulting
- Base and sub-base erosion
- Loss of support

## *Transverse Crack Deterioration from Probable Pumping Action*









# Incompressibles

- Joint spalling
  - Blowups (extreme cases)
- Buckling
- Slab shattering



# Options for a failed joint

- Do nothing
- Short term sealing over existing material
- Remove and replace with similar material
- Remove and replace with different material





# Sealing Methods

## □ HOT APPLIED

- Polymer Modified Hot applied sealant

## □ COLD APPLIED

- Single and two-component or preformed materials
- Silicone, non-sag or self-leveling



PETROLEUM  
BASES



GROUND  
RUBBER



ELASTIC  
MODIFIERS



REINFORCING  
AGENTS



ADDITIVES

SPECIFICATION SEALANTS



NON-SAG



SELF-LEVELING

LOW MODULUS SILICONE



# Joint Prep Equipment

- Hook or plow for removing existing sealant
- Wire wheel
- Concrete saw for sealant removal and refacing sidewalls of the joint
- Water or abrasives blaster
- Compressed Air, hot &/or cold
- Backer Rod tool for installation






# Equipment (Hot-Applied)

- Indirectly heated double boiler type Melter/ Applicator.
- Thermostatic Controlled heating system
- Heated Sealing Hose is available.
- Effective agitation and material recirculation.
- Proper wand tip for desired application.



# Oil Jacketed Melter/ Applicator







## Equipment (Cold- Applied)

- ❑ Single and two-component materials
- ❑ Verify pump is in proper working order
- ❑ Verify two-component pump is delivering material at the correct ratio.
- ❑ Use the appropriate wand tip.
- ❑ Hoses are not plugged.







# Joint Preparation Process

- The *most important factor* in the resealing process.
- Remove all existing materials
- Saw or reface side walls to clean up and reshape the joint
- Clean thoroughly with forced air/ water and/ or wire wheel to receive new material.
- Install backer rod





















# Joint Preparation

- CLEANING (After removing most sealant)
  - Hook out and remove majority of sealant
  - Use saw to reshape, score and remove any residual sealant
  - After sawing, joints are flushed with high pressure water to remove all slurry and debris.
  - Joint is cleaned with abrasive cleaning or wire brushing.
  - Use two passes of abrasive air, each directed at one of the joint faces.



# Joint Preparation

## □ CLEANING

- Joint is blown with clean *dry* air.
- Compressor must have functioning oil/moisture filter/trap.
- Use of a Heat Lance is often effective
- Compressor should have sufficient pressure and volume.





# Joint Preparation

## □ CLEANING

### ■ FINGER TEST

- Inspect joint prior to sealing by running your finger along the walls to insure no moisture or contaminants exist.
- If oil, dried saw slurry or dust are present joint must be re-cleaned.

# Joint Preparation

## □ Backer Rod Installation


- Installed after final cleaning and just before sealing.
- Use backer rod installation tool.
- Use heat resistant backer for Hot applied sealants.
- Backer should fit snugly in joint.
- Do not tear, stretch or damage during installation.





# Properly prepared Joint

(Cross-sectional view)





# Sealant Installation

## □ WEATHER REQUIREMENTS

- Follow Manufacturers recommendations
- Surface temperature typically 4 deg. C (40 deg. F) or warmer for sawing/Sealing.
- Sealing shall not begin if rain is imminent.
- APPLICATION SHOULD NOT BEGIN IF THERE IS ANY SIGN OF MOISTURE IN THE JOINT.



# Sealant Installation (Hot-Applied)

- Follow manufacturers instructions.
- Before Sealing can begin.
  - Melter Heat Transfer Oil is at proper temp.
  - Material is heated to Manufacturers minimum sealing temperature.
  - Sealant is continuously agitated and recirculated prior to application.
- Sealant should be checked periodically to assure proper temperatures are being maintained.






# Sealant Installation (Hot-Applied)

- Melting tank should be kept between 1/3 to 2/3 full to help maintain temperature uniformity.
- Joint should be filled from the bottom up to the specified level to produce a uniform surface with no voids.
  - Use the correct concrete sealing tip.
- Traffic is not allowed on project until sealant is tack-free or cooled.
- Use a sealant barrier spray to speed up traffic opening.

# Properly sealed Joint


□ RECESSED



# Properly sealed Joint (Option 1)

## □ Over-Banded

- 2 pass operation
- 1<sup>st</sup> pass recessed
- 2<sup>nd</sup> pass over-band





## Sealant Installation (Cold-Applied)

- Joint is filled from the bottom up to the specified level with no voids in the sealant.
- Tool non-sag sealants to force the material against the sidewalls and to form a smooth surface.
- Sealant must be permitted to cure to a tack-free condition prior to opening pavement to traffic













# Common Problems / Solutions

- Sealant not adhering to joint sidewalls
  - Joint not clean enough – re-clean
  - Wet joint surfaces – allow to dry
  - Low sealant temp.- Heat to correct temp.
  - Cold ambient temp.- allow temp to rise.
  - Concrete not cured sufficiently – allow to further cure.





# Common Problems / Solutions

- Sealant pick-up or pull-out when opened to traffic
  - Opened to traffic too soon
  - High ambient temperature – seal in cooler temps.
  - Excessive sealant application – apply below surface or specified recess.
  - Overheated or under-heated sealant
  - Sealant contaminated with solvent or petroleum product.
  - Joint faces contaminated with old, incompatible sealant



# Common Problems / Solutions

- Sealant cracking or de-bonding in winter.
  - Sealant too stiff for climate.
  - Poor cleaning during installation.
  - Sealing during extreme hot summer weather.
  - Joint too narrow for movement experienced.
  - Incorrect joint configuration, sealant too thick or too thin.




# Common Problems / Solutions

## □ Voids or Bubbles in cured sealant

- High pavement temp. and moisture content when sealed.
- Outgassing of backer material. –wrong backer rod used.
- Backer rod punctured or damaged during installation.
- Moisture on backer rod from being installed night before – Replace backer rod.





# Joint Sealing reference resources/ websites

- US Department of Transportation
  - Federal Highway Administration
    - [www.fhwa.dot.gov/preservation](http://www.fhwa.dot.gov/preservation)
    - SHRP Report
    - Resealing Concrete Pavement Surfaces
    - Pub no. FHWA-RD-99-137
- Foundation for Pavement Preservation
  - Pavement Preservation Checklist Series
    - Joint Sealing Portland Cement concrete Pavements.
    - [www.fp2.org](http://www.fp2.org)
- ACPA American Concrete Pavement Association
  - [www.pavement.com/pavTech/Tech/fundamentals/fundsealants.html](http://www.pavement.com/pavTech/Tech/fundamentals/fundsealants.html)
- Cimline Inc.
  - Guide to Cracksealing
    - [www.cimline.com](http://www.cimline.com)



---



# Questions?

**Rick Stone**  
**General Manager, Cimline Northeast**  
**518-859-2794 cell**  
**[rstone@cimline.com](mailto:rstone@cimline.com)**

