

Effective repair of severely deteriorated prestressed beam ends

Paul Pilarski, P.E., S.E.

Metro North Region Bridge Construction Engineer


MnDOT Research performed at University of Minnesota

Dr. Carol Shield and Paul Bergson

PS Beam End Repair Research

- Typical concrete repair procedures
- Concerns
- Original repair project
- Research


How are concrete repairs to bridges made?



Step 2: Remove delaminated concrete



Step 3: Supplement corroded reinforcement



Step 4: Replace concrete

Shotcrete: dry cement, sand and aggregate wetted at a nozzle and sprayed at high velocity



Step 4: Replace concrete

Shotcrete: dry cement, sand and aggregate wetted at a nozzle and sprayed at high velocity



Common shotcrete map-crack



Shotcrete often performed without load relief or temporary support





BR 27568 – SB Pier 34



Questions:

- Does the shotcrete restore strength? Or just cover up and protect from additional deterioration? Durability?
- How does lack of load relief affect repair?
- Is there an effective means to preserve prestressed beam ends with internal stresses?

Questions:

- Does the shotcrete restore strength? Or just cover up and protect from additional deterioration? Durability?
- How does lack of load relief affect repair?
- Is there an effective means to preserve prestressed beam ends with internal stresses?

Durability?

"Evaluation of Repair Materials for Use in Patching Damaged Concrete"

Must use compatible patch material

- Match elastic modulus
 - High bond strength
 - Thermal compatibility
 - Compressive strength
- ➔ Must moist cure



Iowa DOT Project TR - 428

Final

REPORT

IOWA STATE UNIVERSITY
OF SCIENCE AND TECHNOLOGY

**Department of Civil, Construction and
Environmental Engineering**

Marquette University
e-Publications@Marquette

Master's Theses (2009 -)

Dissertations, Theses, and Professional Projects

Repair and Strengthening of Bridge Substructures

Steven W. Ainge
Marquette University

Report No.

FWHA/TX-03/1774-2

SP-230-82

**Performance of Corrosion-Damaged RC
Columns Repaired by CFRP Sheets**

by S.-W. Bae, A. Belarbi, and J.J. Myers

Durable Repairs with FRP

UNLV | University Libraries
University of Nevada, Las Vegas

UNLV Theses/Dissertations/Professional Papers/Capstones

12-1-2014

Investigation of Chloride Induced Corrosion of
Bridge Pier and Life-Cycle Repair Cost Analysis
Using Fiber Reinforced Polymer Composites

Dinesh Dhakal
University of Nevada, Las Vegas, dhakad1@unlv.nevada.edu



NATIONAL BRIDGE PRESERVATION PARTNERSHIP CONFERENCE 2018

PRACTICES WE CAN NOT AFFORD TO DEFER

Column repairs (2014 scoping)



unsound removals



shotcrete repair with curing agent



BRIDGE I



Shrinkage
cracks within
year old patch



Questions:

- Does the shotcrete restore strength? Or just cover up and protect from additional deterioration? Durability?
- **How does lack of load relief affect repair?**
- Is there an effective means to preserve prestressed beam ends?

Column repair (ICRI Doc. 310.1R)

- Sustained forces flow through remaining section of concrete and intact vertical reinforcement after removals
- Only LL and other transient forces act on repaired section unless shored during repair

Original Removals




Fig. 10.1: Column load path




Fig. 10.2a: Column repair




Fig. 10.3: Column load path following repair




Fig. 10.2b: Column section

Column repair

- Visualize forces as truss (Strut and tie model)




Fig. 10.3: Column load path following repair

Column repair

- Visualize forces as truss (Strut and tie model)




Fig. 10.3: Column load path following repair

Column repair

- Visualize forces as truss (Strut and tie model)
- External confinement maintains patch ability to sustain additional compression





Fig. 10.3: Column load path following repair

FRP wrapping for confinement and patch longevity



Questions:

- Does the shotcrete restore strength? Or just cover up and protect from additional deterioration?
- How does lack of load relief affect repair?
- Is there an effective means to preserve prestressed beam ends?


Repair of Bridge 27568

US Route 169 over Nine Mile Creek




Scoped 2011-12
Contract work 2013

Bridge 27568: Nine Mile Creek Location



Br. 27568

- TH 169 over Nine Mile Creek in Edina, MN
- Built by Hennepin County in 1974
- Spans over poorly drained wetland above old roadbed(s)




Bridge
27568

Wetland



Structure Background



- 60' spans
- 49 Prestressed beam spans
- Prestressed concrete pile bent piers

Preservation Scoping 2011: Beam ends at joint locations



NATIONAL BRIDGE PRESERVATION PARTNERSHIP CONFERENCE 2018

PRACTICES WE CAN NOT AFFORD TO DEFER

Variety of deterioration levels



Beam End Repairs - Small

NB Pier 10 Fascia



Beam End Repairs - Small



NB Pier 34 East Fascia



Beam End Repairs - Large

Pier 16: Large repair - Shotcrete repair without support




Beam End Repairs - ~~Large~~ ^{Medium}

Pier 16: ~~Large~~ repair - Shotcrete repair without support
Medium




Change of Plan



Beam End Repair - Large



Michigan DOT Detail for End Repair



Michigan DOT
 Research Report R-1380
 January 6, 2000

Michigan DOT Detail for End Repair

Michigan DOT Research Report R-1373, Sept 1999

- MDOT and FHWA personnel drafted a 1999 repair procedure
- Repair procedure was performed in our laboratory on a salvaged prestressed I beam.
- Beam was load-tested
- Conclusion: ***Up to 1 stirrup and 12" of strands may be exposed without prestress or shear strength loss***



10/21/2013 11:02

Damage beyond Michigan Conclusions




Damage beyond Michigan Conclusions




10/21/2013 11:05

Box Type Repair (Large Repair)



Full DL relief can be detrimental to internal force balance!

















10/21/2013 11:17



10/21/2013 11:16



10/21/2013 10:56







10/21/2013 13:05



10/21/2013 13:03



10/21/2013 11:18











10/21/2013 15:19



10/21/2013 16:03











Collins

1826S

10/22/2013 10:36











10/22/2013 10:28



10/22/2013 10:35



10/22/2013 10:36



10/22/2013 10:38











10/22/2013 11:16



10/22/2013 11:34



10/22/2013 13:09





10/22/2013 13:19



10/22/2013 13:21





10/22/2013 13:46









10/28/2013 08:50





Other deteriorated components





07/25/2013

Pile deterioration





07/25/2013



07/25/2013



07/25/2013







How do we assess adequacy?

- Small scale testing.
- Industry research on shotcrete bond.
- Observations during destruction.
- Monitoring for cracks and crack growth

Other DOT's and Agencies: 2015 WisDOT



Other DOT's and Agencies: USACE



Bridge replaced in 2017 due to high risk deterioration in piling and beams

➔ Opportunity!!!

Research money sought and awarded:

Verify beam repair restored strength to original capacity or better

Beam End Research

- Salvage 2 repaired beams
- Salvage 2 unrepaired beams
- Load test all four – record crack patterns and failure progression
- Compare strength

Beam End Research

Hurdles:

- Sawcut to suitable length for U of M Civil Engineering Laboratory
- \$35K salvage and transport estimate from contractor of new causeway
- Cast narrow 10,000 psi deck on beams (Required to ensure a failure in the beam end rather than center)

Salvage and Transport



NATIONAL BRIDGE PRESERVATION PARTNERSHIP CONFERENCE 2018

PRACTICES WE CAN NOT AFFORD TO DEFER

Girders at lab



GE PRESERV

P₄ – End View

Cast 10,000 psi narrow deck in lab




NATIONAL BRIDGE PRESERVATION PARTNERSHIP CONFERENCE 2018

PRACTICES WE CAN NOT AFFORD TO DEFER

Experimental Setup

- 36'-1.5" span, original bearing pads at original CL bearing
- Load applied at 13'-3" from end



Experimental Setup

- External shear stirrup system to prevent cut end failure
- 50 kips initial load
- Displacement controlled loading (0.06"/minute)
- Stop at 25 kips increments to map cracks




Made by Paul Pilarski, MnDOT Bridge Office




- Peak load = 465 kips
- 1st flexural crack = 300 kips
- 1st web shear crack = 325 kips



- Peak load = 451 kips
- 1st flexural crack = 275 kips
- 1st web shear crack = 350 kips



Girder P₄ and Girder P₂ Results



AASHTO LRFD predicts $V_n=204$ kips

Girder P4 (Repaired)

- V_u LL = 302 kips
- V_u DL = 14 kips
(at closest stirrup failure to girder end)

Girder P2 (unrepaired)

- V_u LL = 293 kips
- V_u DL = 12 kips (at closest stirrup failure to girder end)

Girder P26 (repaired)

- V_u LL = 323 kips
- V_u DL = 14 kips
(at closest stirrup failure to girder end)

Girder P24 (unrepaired)

- V_u LL = 320 kips
- V_u DL = 12 kips (at closest stirrup failure to girder end)

Beam End Repair Cost

- 2013 Beam end shotcrete surface repair- EACH beam end, *not* square foot area. Bid cost = \$755.
 - ➔ Included bearing jacking cost
 - 2017 Shotcrete repairs typically \$160/SF
- ## Beam End “Reconstruction”
- 2013 by S.A. \$5.5K Each (Qty = 2)
 - 2016 by S.A. \$12.5K Each (Qty = 2)
 - 2017 by contract \$10,000 Each (Qty=5)
- ➔ Shoring extra

Thanks are due!

- MnDOT Research Services
- Ames Construction
- U of M Civil Engr. Dept.
- Eden Prairie Bridge Maintenance
- David Kogler, GV Bridge inspector
- PCI Roads (Repair Contractor)



PS Beam End Repair Testing

<http://www.dot.state.mn.us/research/index.html>

Questions?

Full report #2018-07,
published 03/12/2018

m DEPARTMENT OF TRANSPORTATION **511**

Search MnDOT A to Z General Contacts

Research Projects

We put your ideas in motion

Home About News Publications **Projects** RFP/Contracts Resources Contact

Search Projects:

Browse by:

- [Year](#)
- [Category](#)
- [Researcher\(s\)](#)
- [Technical Liaison\(s\)](#)

Search MnDOT and the Local Road Research Board's research projects ?

Search for: 2018-07

Category: All available categories

Year: All available years

Search