

Project Selection Criteria for In-Place Recycling


**Northeast & Mid Atlantic
In-Place Recycling Conference
August 24, 2010**

Sohila Bemanian, PE
Parsons Transportation Group




Why In-Place recycling?

Meets the 3E Challenge




Timing of Rehabilitation Techniques

(The Right Project, at The Right Time, and The Right Strategy)



Pavement Preservation



What is a good strategy for surface raveling?

HIR



What is a good strategy for medium and wide transfers and black cracking?



What is a good strategy for alligator cracking?



Project Selection Criteria

1. Existing pavement condition and design
 - Distress type, level, and extent
 - Traffic Loading
1. Environmental condition
2. Roadway geometry
3. Project site consideration




Additional Factors to Consider

(continued)

- 5. Initial funding constraint
- 6. Life-cycle cost based on long-term performance
- 7. Traffic Control



1. Existing Pavement Evaluation



Engineering Requirements

◆ Subsurface Investigation:

- ◆ Coring to determine pavement thickness



- Look for lift locations
- Digout thickness
- Deep lifts of asphalt concrete
- fabric

Pavement Thickness Design

- Using either MEPDG
or
1993-AASHTO Design Guide
- Use structural number 0.28-0.35 for CIR
- Mr. for CIR varies from low 200's to 1 M
- Do not want to make it too high strength
- Calculate projected traffic loading for the design life

Structural Layer Coefficient

FDR Method	Minimum Thickness of Riding Surface	Typical Structural Coefficient
Mechanical	2" HMA	0.10 – 0.12
Bituminous	Surface Treatment or Structural HMA	0.20 – 0.28
Cement	Surface Treatment or Structural HMA	0.15 – 0.20

Mix Design Process




1) RAP: Cores or Grindings from Project	Cores or Milling are crushed to passing 1"
2) Mixing	3 emulsion contents and H ₂ O content are made
3) Compaction	Use Gyratory Compactor
4) Curing of Specimens	48 hours
5) Cured Specimens Measurements	2 sets: dry and soaked
6) Mix Design Selection	Determine optimum emulsion content

Mix Design Process



Gyratory Compactor



Marshall Stability



Raveling Test



RAP Preparation

Project Selection Criteria

1. Existing pavement condition and design
 - Distress type, level, and extent
 - Traffic Loading
1. Environmental condition
2. Roadway geometry
3. Project site consideration



2. Environmental Condition

(Climate conditions must be considered when selecting in-place recycling)

Factors to consider

- Good drainage is a MUST
- Type and thickness of the wearing surface (Slurry seal, Double chip seal, hot mix overlay, and friction course)
- PG grade binder



I-80 Pequop

NCHRP Synthesis 40-13

Ranking of climates which can influence the choice of in-place recycling processes

Climate	HIR	CIR	FDR
Cold/Wet	Fair	Good	Very Good
Hot/Wet	Good	Good	Very Good
Cold/Dry	Good	Very Good	Very Good
Hot/Dry	Very Good	Very Good	Very Good

Project Selection Criteria

1. Existing pavement condition and design
 - Distress type, level, and extent
 - Traffic Loading
1. Environmental condition
2. Roadway geometry
3. Project site consideration



3. Roadway Geometry

- Profile grade
- Drainage ditches
- Guard rail
- Overhead
- Cross slope



Kingsbury Grade, Nevada
10% grade



Project Selection Criteria

1. Existing pavement condition and design
 - Distress type, level, and extent
 - Traffic Loading
1. Environmental condition
2. Roadway geometry
3. Project site consideration



4. Project Site Consideration

- Contractors availability
 - Contact ARRA - www.arra.org
- Project length
 - At least 4 miles for HIR and CIR
- Construction season

Additional Factors to Consider

(continued)

- 5. Initial funding constraint
- 6. Life-cycle cost based on long-term performance
- 7. Traffic Control



5. Initial Funding Constraint

In-place recycling can meet both initial and life cycle cost constraint

	3" CIR & 1.5" HMA	3" Mill & 3" HMA
GF	$3(1.5 - 1.25) + (1.5" \times 2.25) = 4.125$	$3 \times (2.25 - 1.25) = 3$
Cost	<p>CIR: 50,688 S.Y. @ \$2.30 = \$116,582</p> <p>Recycling Binder: 196 tons @ \$535 = \$104,860</p> <p>1.25 inch HMA Overlay 3,659 tons @ \$95.00 = \$347,605</p> <p>TOTAL: \$569,047</p>	<p>Rotomill: 50,688 S.Y. @ \$1.50 = \$76,032</p> <p>HMA: 8,781 tons @ \$95.00 = \$834,195</p> <p>TOTAL: \$910,227</p>
	CIR & HMA provides 37% less cost	GF for MNDOT New HMA = 2.25 CIR = 1.5 Existing HMA = 1.25
	Save \$341,180 37% increase in SN	

5. Initial Funding Constraint

(Nevada DOT Cost Comparison)

Category	ESALs	Strategy	Total GRAVEL FACTOR Numbers	Strategy Cost	Reduced Cost/ Mile	Change in SN
LOW	< 1 Million	2" Mill & fill	$2''(0.35-0.18)=0.34$	625K	63%	(12%)
		3" CIR Double Chip Seal	$3(0.28-0.18)=0.30$	230K		
MEDIUM	> 1 Million < 3 Million	3" Mill 3" HMA	$3''(0.35-0.18)=0.51$	910K	37%	60%
		3" CIR 1.5" HMA	$3''(0.28-0.18)+1.5'' \cdot 0.35=0.82$	570K		
HIGH	> 3 Million	3" Mill 6" HMA	$(6'')(0.35)-(3'')(0.18)=1.56$	1.82 M	28%	10%
		3" CIR 4" HMA	$3(0.28-0.18)+4(0.35)=1.70$	1.3 M		

Additional Factors to Consider

(continued)


- 5. Initial funding constraint
- 6. Life-cycle cost based on long-term performance
- 7. Traffic Control



6. Life-cycle Cost Analysis

Present Worth for Pavement Rehabilitation

State-of-the-Practice on CIR and FDR Projects
NDOT, Nov. 21, 2005



Long-Term Performance

7-year Performance

CIR and 2" Overlay Section, Reno, Nevada



Additional Factors to Consider

(continued)

- 5. Initial funding constraint
- 6. Life-cycle cost based on long-term performance
- 7. **Traffic Control**



7. Traffic Control

Extremely Important

Factors to consider:

- Day time vs Night time construction
- ADT and type of traffic (cars vs trucks)
- Opening to traffic
- Intersections and other stop and go
- Access to local business



CIR on I-80 in Nevada



Agency: NDOT District 3
Contractor: Road & Highway Builders
Subcontractor: Valentine Surfacing
2007-2008

In-Place Recycling Websites

- www.greenroads.us
- www.fhwa.dot.gov/
- www.pavementpreservation.org/video/index.p
- www.dot.ca.gov/hq/esc/Translab/ope/CIPR.h
- www.transportation.org/
- www.fp2.org/
- www.pavementrecycling.com

Recommendations

- Agencies should consider HIR, FDR and CIR in their tool box
- Start slowly and get contractors involved early
- Continue improving the process




Conclusions

HIR, CIR and FDR Meet the 3E Challenge

Sustainability

Energy Use Per Tonne Of Material Laid Down



Source: *The Environmental Road of the Future, Life Cycle Analysis* by Clappert, M. and Julian Bilal, Colas Group, 2003, p.34

20-Yr CIR Performance



\$600M Cost-Saving with
CIR and FDR



Let's Create a Sustainable Future!

Sohila Bemanian, PE
Parsons Transportation Group
Carson City, Nevada

Sohila.bemanian@parsons.com

(775) 297-6515

